

POOL WATER TESTING WATER TEST KITS - PHOTOMETERS



“Green Chemistry”

Lovibond is committed to improving the environment - reagents that are easy to use, that are safe, have a long and stable shelf-life, are extremely accurate, provide reproducible results, and are environmentally friendly.

- * 100% free of Boric Acid
- * Exact reagent quantity
- * DIN EN ISO 7393-2 Compliance
- * Optimal pH buffer system
- * Strict quality monitoring & assurance

Test Tablets for Lovibond Photometers

Code	Description	Price	Code	Description	Price	
WT37	DPD No 1	Box of 250	14.00	Calcium Hardness:		
WT337	DPD No 2	Box of 250	16.30	WT461	Calcheck	
WT38	DPD No 3	Box of 250	14.00	WT431	Calcio Combi Pack	
WT384	DPD No 4	Box of 250	19.00		Calcio H No.1 & No.2 tablets	
WT39PH Phenol Red	Box of 250	14.00	WT444	Cyanuric Acid	Box of 250	
			WT57C	Copper Combi Pack	2 Boxes of 250	
	High Calcium Levels: Over 500mg/l			Copper No.1 & No.2 tablets		
WT37H	DPD No.1 High Calcium*	Box of 250	18.00	WT67	Iron LR	Box of 250
WT38H	DPD No.3 High Calcium*	Box of 250	18.00			
	High Chlorine Levels: 0 - 10ppm:			Ozone:		
WT37HR	DPD No.1 High Range	Box of 250	14.00	WT384	Oxygen - DPD No.4	Box of 250
WT38HR	DPD No.3 High Range	Box of 250	15.00	WT562	Glycine Tablets	Box of 100
	Bromine:			WT72C	Phosphate LR 1 & 2	2 Boxes of 100
WT37	DPD No.1	Box of 250	14.00			
	Alkalinity:			Sodium Hypochlorite:		
WT451	Alka-M	Box of 250	23.50	WT98	Chlorine High Range	Box of 100
				WT99	Acidifying Tablets	Pack of 250
						22.80

Reference Standards for Lovibond Photometers

Code	Description	Price
MD100 / MD200 Photometers:		
275655	Ref Standard - Chlorine 0.5 / 2.0mg/l	50.18
275670	Ref Standard - pH 7.45	40.72
PM600 / PM630 Photometers:		
215630	Ref Standard - Chlorine 0.5 / 2.0mg/l	50.73
215665	Ref Standard - pH 7.45	42.40

Reference Standards are designed to check the accuracy of your photometer

Lovibond offers a Laboratory Photometer Calibration Service if required.



LOVIBOND TurbiCheck with infra-red light source (EN ISO 7027)

Code	Description	Price
WT08	TurbiCheck - Infra-red Turbidity Meter	633.00
	Instrument supplied in carrying case, 4 turbidity standards (<0.1, 20, 200 & 800NTU), 9v Battery, 2 Vials (24mm dia.) with lids, Guarantee sheet, Certificate of Compliance & Instruction Manual. (19 41 50)	
	The compact Lovibond infra-red turbidity meter TurbiCheck is designed to allow fast, precise on-site testing. The unit measures the scattered light at an angle of 90 degrees, as stipulated to EN ISO 7027.	
WT64	Set of 12 empty vials - 24mm dia. (19 76 555)	77.00



Spares for Photometers

Code	Description	Price
WT191	Lovibond (PCCheckit) Round Glass 10ml - Each	5.50
WT196	Box of 12 x WT191	54.00
WT22	Test Tube Brush	2.10
WT23L	Plastic Crusher - long (130mm long)	1.60
WT20	10ml Syringe	1.50
WT112	Lid for Battery Housing (whilst stocks last)	7.50
WTB	Alkaline Battery	3.50

