

Universal Joint Request for Quotation

<p>BORE SIZE AND CONFIGURATION LEFT END</p> <p>MALE _____ FEMALE _____</p> <p></p> <p>PLAIN _____</p> <p></p> <p>KEYWAY _____</p> <p></p> <p>HEXAGONAL _____</p> <p></p> <p>SQUARE _____</p> <p></p> <p>THREADED _____</p> <p></p> <p>SPLINE _____</p> <p></p>	<p><i>DOUBLE UNIVERSAL JOINT (TELESCOPING VERSION SHOWN)</i></p> <p><i>SINGLE UNIVERSAL JOINT</i></p> <p>BOOTS SHOWN FOR REFERENCE, BUT ARE OPTIONAL.</p>	<p>BORE SIZE AND CONFIGURATION RIGHT END</p> <p>MALE _____ FEMALE _____</p> <p></p> <p>PLAIN _____</p> <p></p> <p>KEYWAY _____</p> <p></p> <p>HEXAGONAL _____</p> <p></p> <p>SQUARE _____</p> <p></p> <p>THREADED _____</p> <p></p> <p>SPLINE _____</p> <p></p>
---	---	--

Joint to be used for:			
Nature of operation:	Continuous: <input type="checkbox"/>	Intermittent: <input type="checkbox"/>	
Operating temperature:	Maximum:	Minimum:	Average:
Operating environment:	Abrasive: <input type="checkbox"/>	Corrosive: <input type="checkbox"/>	Clean: <input type="checkbox"/> Other:
Actual horsepower:	Torque:	RPM:	
Angle of operation:	Maximum:	Minimum:	Average:
Center connection:	Axially free: <input type="checkbox"/>	Axially free w. retaining ring: <input type="checkbox"/>	W. spring + retaining ring: <input type="checkbox"/>
Boots:	Booted: <input type="checkbox"/>	Unbooted: <input type="checkbox"/>	
Material:	Alloy: <input type="checkbox"/>	Stainless: <input type="checkbox"/>	Other:
Finish:	Cadmium: <input type="checkbox"/>	Nickel: <input type="checkbox"/>	Zinc: <input type="checkbox"/> Black Oxide: <input type="checkbox"/> Other:
Quantity:			
Name:		Company:	
Address:			
City:		Postal code:	Country:
Telephone:		Fax:	
E-mail:			

Please copy and fax to your Belden contact. (For details see contact info at the end of the catalog)