

Punta in metallo duro senza canalini per acciaio inox
Foret carbure sans trous d'huile pour acier inox
Hartmell-Bohrer ohne IK für Edelstahl
Carbide drill without coolant holes for stainless steel

高性能ドリル7× D、ストロングシャンク


高性能右旋螺旋钻，有加强柄

TTD 207

SMG SP Z 2

TUSA NORM RH

7×D TIALN



Campo d'impiego / Champ d'application / Einsatzbereich / Application field / 応用範囲 / 應用

HRC < 60	Inox Stainless	GG(G)/ghisa Ft/cast iron	Titanio Titan	ALU
----------	----------------	--------------------------	---------------	-----

d1	h5	d2	h6	l1	l2	d1	h5	d2	h6	l1	l2
0,80	3,0	5,8	53			1,90	3,0	13,8	53		
0,85	3,0	6,2	53	*		1,95	3,0	14,1	53	*	
0,90	3,0	6,5	53			2,00	3,0	14,5	53		
0,95	3,0	6,9	53	*		2,05	3,0	14,9	53	*	
1,00	3,0	7,3	53			2,10	3,0	15,2	53		
1,05	3,0	7,6	53	*		2,15	3,0	15,6	53	*	
1,10	3,0	8,0	53			2,20	3,0	16,0	53		
1,15	3,0	8,3	53	*		2,25	3,0	16,3	53	*	
1,20	3,0	8,7	53			2,30	3,0	16,7	53		
1,25	3,0	9,1	53	*		2,35	3,0	17,0	53	*	
1,30	3,0	9,4	53			2,40	3,0	17,4	53		
1,35	3,0	9,8	53	*		2,45	3,0	17,8	53	*	
1,40	3,0	10,2	53			2,50	3,0	18,1	53		
1,45	3,0	10,5	53	*		2,55	3,0	18,5	53	*	
1,50	3,0	10,9	53			2,60	3,0	18,9	53		
1,55	3,0	11,2	53	*		2,65	3,0	19,2	53	*	
1,60	3,0	11,6	53			2,70	3,0	19,6	53		
1,65	3,0	12,0	53	*		2,75	3,0	19,9	53	*	
1,70	3,0	12,3	53			2,80	3,0	20,3	53		
1,75	3,0	12,7	53	*		2,85	3,0	20,7	53	*	
1,80	3,0	13,1	53			2,90	3,0	21,0	53		
1,85	3,0	13,4	53	*		2,95	3,0	21,4	53	*	
						3,00	3,0	21,8	53		

Disponibili su richiesta*
Min. 5 pz

Disponible sur demande*
Au moins 5 pièces

Available on request*
Minimum qty 5 pcs

Verfügbar auf Anfrage*
Mindestmenge 5 Stk