

AQUA ENERGY

**Skid Mounted, Electric Driven
High & Ultra Pressure Water Jet Units
Choice of Sound Attenuated Canopies & Offshore Crash-Frames
All models conform to CE & offshore Regulations**

Model: ES-50



**PERFORMANCE
OPTIONS**

2,758 bar @ 06.80 l/min
1,500 bar @ 12.70 l/min
1,200 bar @ 16.90 l/min
1,100 bar @ 17.30 l/min
800 bar @ 25.00 l/min
600 bar @ 30.00 l/min
500 bar @ 38.00 l/min
400 bar @ 45.00 l/min
280 bar @ 74.00 l/min

Model: ES-50 Rear View

**PERFORMANCE
OPTIONS**

2,758 bar @ 06.80 l/min
1,500 bar @ 12.70 l/min
1,200 bar @ 16.90 l/min
1,100 bar @ 17.30 l/min
800 bar @ 25.00 l/min
600 bar @ 30.00 l/min
500 bar @ 38.00 l/min
400 bar @ 45.00 l/min
280 bar @ 74.00 l/min



**Aqua Energy International Limited, 28 St James Business Centre, Linwood Road
Paisley PA3 3AT, Scotland, UK**

Tel: (+44) (0) 141 849 6888 Fax: (+44) (0) 141 848 5777

E-mail: sales@aquaenergy.com www.aquaenergy.com

Standard Features

Pump- Horizontal triplex positive displacement pump rated up to 52HP service. Plunger pump consists of Stainless Steel Fluid Head. Stainless steel valves, seats, springs and stainless steel plungers with ceramic coating. The plungers and packing are water lubricated. The power end of the pump is positive splash oil lubricated with sight glass for oil level check. Crankshaft is gas nitrated, hardened and tempered alloy steel. Main bearings are roller.

Suction Plumbing- 1" Female BSP inlet port.

Two easy clean 1 to 25 micron water filters ensures a clean water supply to the pump.

Discharge Plumbing- Discharge manifold with ½" FBSP outlet port.

Glycerine filled pressure gauge and safety rupture disc.

Unit Mounting- Mounted on a steel channel frame with pump base and adjustable motor base.

Motor: ABB or similar, Control Panel and motor to Star Delta Start.

Power Transmission- Pump and engine connected via a reduction gearbox or a non-slip belt drive with safety guard.

Finish System- All unpainted surfaces are hot dipped and galvanised.

Left galvanised or Aqua Energy Blue or to the customers colours.

Optional Accessories:

Gun- Hand or foot dump control type with safety shroud, whip hose and coupling.

Hoses- Ultra high pressure for use at pressures up to 4000 bar.

Lances- Rigid and flexible variety SAE, JIC, pipe and welded end connections.

Nozzles- Wide assortment for surface and tube cleaning.

Pressure Control Valve- Variable flow and pressure adjustment. Controlled by hand or mechanical actuation.

Auto-Throttle- Variable engine speed adjustments with automatic return to idle when Aqua-Gun is depressurised.

Vacuum- Uses the Jet-Blaster pump to create a vacuum for sludge and slurry transport.

Line Mole- Pipe and sewer cleaning type with replaceable fan and round jet inserts.

Abrasive Injector- Aqua-Saw abrasive injector mixes abrasive into Aqua-Gun discharge stream.

Deck Cleaner- Rotary jet driven multi-nozzle floor and grate cleaning system with hand operated controls.

Couplings- Quick disconnect Acme thread rated at up to 20,000 psi working pressure. Optional snap type for use to 10,000 psi.

For further information contact: Aqua Energy International Limited
28 St James Business Centre
Linwood Road, Paisley PA3 3AT
Scotland, UK
Tel: (+44) (0) 141 849 6888
Fax: (+44) (0) 141 848 5777
E-mail: sales@aquaenergy.com
www.aquaenergy.com