

AQUA ENERGY

Trailer Mounted High Pressure Water Jetting Units Option of Fully Acoustic Sound Attenuated Canopies

All models conform to European Union Road Regulations
Also designed for Oil Refinery & Gas Plant Applications

MODEL: DT-180



PERFORMANCE OPTIONS

2,758 bar @ 24.00 l/min
1,500 bar @ 44.00 l/min
1,300 bar @ 52.00 l/min
1,100 bar @ 63.00 l/min
900 bar @ 72.00 l/min
800 bar @ 84.00 l/min
700 bar @ 96.00 l/min

PERFORMANCE OPTIONS

2,758 bar @ 24.00 l/min
1,500 bar @ 44.00 l/min
1,300 bar @ 52.00 l/min
1,100 bar @ 63.00 l/min
900 bar @ 72.00 l/min
800 bar @ 84.00 l/min
700 bar @ 96.00 l/min

MODEL DT-180



Aqua Energy International Limited, 28 St James Business Centre, Linwood Road
Paisley PA3 3AT, Scotland, UK

Tel: (+44) (0) 141 849 6888 Fax: (+44) (0) 141 848 5777

E-mail: sales@aquaenergy.com www.aquaenergy.com

Standard Features

Pump- DT-180 horizontal triplex positive displacement pump, rated up to 180 Horsepower service. Plunger pump consists of stainless steel fluid cylinders, solid ceramic plungers, stainless steel valves and seats with chevron packing. The plungers and packing are water lubricated. The power end of the pump is positive splash oil lubricated with sight glass for oil level check. Crankshaft is made of high strength alloy steel. Main bearing is roller.

Suction Plumbing- Water filter from 1 to 50 micron capacity protects pump.
250 to 500 litre water storage tank with ball valve and float and low water level engine shut down.

Discharge Plumbing- Discharge manifold with interchangeable high pressure discharge connections for pressure gauge, relief valve, rupture disc and hose couplings. Stainless steel glycerine filled pressure gauge, stainless steel snubber assembly, Rupture disc or relief valve.

Unit Mounting- Mounted on a fully compliant European Union road regulation trailer.

Power Transmission- Direct Drive via a 1500 or 1800 rpm reduction gearbox.

Finish System- Units are hot dipped & galvanised.

Powder coated in Aqua energy blue or to the customers colours.

Engine: Doosan, Perkins or Volvo, Chalwyn Valve, Spark Arrestor or to Zone-2 Specifications

Optional Accessories:

Gun- Hand or foot dump control type with safety shroud, whip hose and coupling.

Hoses- High Pressure for use at pressures up to 4000 bar.

Lances- Rigid and flexible variety SAE, JIC, pipe and welded end connections.

Nozzles- Wide assortment for surface and tube cleaning.

Rotary- Surface Preparation Jet for coatings removal and descaling

Regulator- Variable flow and pressure adjustment. Controlled by hand or mechanical actuation.

Auto-Throttle- Variable engine speed adjustments with automatic return to idle when Aqua-Gun is depressurised.

Vacuum- Uses the Jet-Blaster pump to create a vacuum for sludge and slurry transport.

Line Mole- Pipe and sewer cleaning type with replaceable fan and round jet inserts.

Abrasive Injector- Aqua-Saw abrasive injector mixes abrasive into Aqua-Gun discharge stream.

Deck Cleaner- Rotary jet driven multi-nozzle floor and grate cleaning system with hand operated controls.

Couplings- Quick disconnect Acme thread rated at up to 20,000-psi working pressure. Optional snap type for use to 10,000 psi.

For further information contact: Aqua Energy International Limited
28 St James Business Centre
Linwood Road,
Paisley PA3 3AT, Scotland UK
Tel: (+44) (0) 141 849 6888
Fax: (+44) (0) 141 848 5777
E-mail: sales@aquaenergy.com
www.aquaenergy.com