

HP220 DS-B

HP Water Jetting Unit



Doosan PU086T Engine (140kW/188hp)

65lpm at 1000bar
(17gpm at 14,500psi)

49lpm at 1400bar
(13gpm at 20,300psi)

Doosan PU086TI Engine (197kW/265hp)

83lpm at 1000bar
(22gpm at 14,500psi)

62lpm at 1400bar
(16gpm at 20,300psi)

Refer to the HP220 pump data sheet for alternative performances

HP220 DS, diesel driven, skid mounted, High Pressure water jetting unit, suitable for a wide range of applications. Simple mechanical engine suitable for use in non-regulated regions of the world, making this unit very easy to operate and maintain.

Suitable for single or twin gun / footvalve operation. Applications include surface cleaning, descaling, hydro-demolition, heat exchanger / pipe cleaning, vessel cleaning, subsea cleaning and more.

Dimensions

2.2m long x 1.2m wide x 1.8m high
(87" long x 47" wide x 71" high)

Weight

1,850kg
(4,070lb)

Features

- HP220 pump with pressure lubrication & oil cooling
- Stainless steel pumphead, solid ceramic or carbide plungers, integral gearbox & SAE engine adaptor
- Analogue pressure gauge
- Burst disc assembly
- Doosan 6 cylinder, mechanical engine suitable for use in non-regulated regions of the world (not Europe/North america)
- Simple auto-shutdown control panel.
- Pump switches for low inlet pressure, low oil pressure & high oil temperature
- Polypropylene water tank, boost pump & dual filtration
- Manual pressure adjusting valve
- Fabrications are grit blasted & powder coated with a zinc rich primer & durable topcoat suitable for use in corrosive environments
- Polypropylene diesel fuel tank

Build Options

- Spark arresting exhaust silencer
- Chalwyn valve
- Manual or pneumatic control valve c/w compressor
- site trailer (trolley)
- Proprietary road trailer
- Mounted in a 10' container (standard or DNV)
- Alternative engines (Tier 3, 4 or non-compliant)
- Full range of accessories for all applications