

HP65 EC HP Water Jetting Unit



HP65 ES skid mounted, electric motor driven, High Pressure water jetting unit.

Suitable for a range of applications including surface cleaning, descaling, heat exchanger / pipe cleaning, vessel cleaning and more.

37kW (50hp) Motor	
50Hz	60Hz
27lpm at 650bar	33lpm at 600bar
(7.2gpm at 9,425psi)	(8.7gpm at 8,700psi)
18lpm at 1000bar	22lpm at 900bar
(4.8gpm at 14,500psi)	(5.8gpm at 13,050psi)

45kW (60hp) Motor	
50Hz	60Hz
34lpm at 650bar (8.9gpm at 9,425psi)	33lpm at 650bar (8.7gpm at 9,425psi)
23lpm at 1000bar (6.0gpm at 14,500psi)	22lpm at 1000bar (5.8gpm at 14,500psi)

Refer to the HP65 pump data sheet for alternative performances

Dimensions (approx.)

1.8m long x 1.0m wide x 1.5m high (71" long x 39" wide x 59" high)

Weight (approx.)

625kg (1,375lb)

Features

- HP65 pump with oil cooling
- Stainless steel pumphead, hard wearing plungers & integral gearbox
- Transducer or analogue pressure gauge for display of discharge pressure
- · Burst disc assembly (or safety valve)
- IE3, foot mount, 4 pole electric motor.
 IP55, Class F insulation, Class B rise,
 TEFC. Fitted with PTC thermistors.
 Suitable for 400v/3ph/50Hz &
 480v/3ph/60Hz.
- Pump switches for low inlet pressure & high oil temperature
- Stainless steel water tank, boost pump & dual filtration
- Star delta starter control panel c/w interlocked isolater, start/stop buttons, hours counter, shutdown circuit for pump switches & E-stop. PILZ safety relay & terminals for a remote E- stop. Mounted in a coated sheet steel enclosure with a IP65 rating.
- Manual pressure adjusting valve
- Fabrications are grit blasted & powder coated with a zinc rich primer & durable topcoat suitable for use in corrosive
- environments

Build Options

- Pneumatic control valve
- Air compressor
- The modular design allows any combination of chassis to be configured including Skids, Crashframes, Site Trailers (Trolleys), with or without Enclosures
- · Certified crashframe
- ATEX Zone 1 or 2 electric motors & starter panels
- Full range of accessories for all applications



Skid Option



Enclosed crashframe option



Mounted with castors



Spring Gardens, Washington, West Sussex, RH20 3BS United Kingdom



