

NVR 4 FLUSSI PER TELECAMERE FINO A 5 MEGAPIXEL

WS-N9304



4CH H.265 5MP NVR

- 1.H.265 High profile compression algorithm ideal for Network NVR
- 2.Realtime live display up to 4 IP CAMERAS
- 3.Pentaplex function:live,recording,playback,backup & remote access;
- 4.Support Dual-streams.Multiple control methods,Smart video detection
- 5.Smart camera settings:privacy masking,camera lock,color setting,and tittle display
- 6.Pan Tilt Zoom and Speed Dome Control
- 7.Smart HDDs Management:non-working HDD hibernationg,HDD faulty alarm,Raid function
- 8.Support DHCP / PPPOE / FTP / DNS / DDNS / NTP / Email alarm / IP right management / IP search / network alarm center functions,
support web client, standalone client and SDK.
- 9.Enable strong multi-way synchronization with max 1 channel playback
10. Support Onvif, Alarm, cloud(xmeye.net),no need to do router

NVR 4/8 FLUSSI PER TELECAMERE FINO A 1080P

WS-N9104 WS-N9108



WS-N9104

Key Features:

Encode: Resolution 4CH 1080P, Realtime
Playback: 2*1080P
Support: Cloud Service: One step on the Internet
Support: Remote Client, Mobile, CMS, IE ,
Firefox, Crown, Safari
Support: iPhone, Windows Mobile, BlackBerry,
Symbian, Android
Support: ONVIF, HDMI, Multi-language
Support: P2P, Cloud software
HDD Capacity: 2*4TB

WS-N9108

Key Features:

- 1.H.264 High profile compression algorithm ideal for Network NVR
- 2.Realtime live display up to 8 IPCAMERAS
- 3.Pentaplex function:live,recording,playback,backup & remote access;
- 4.Support Dual-streams,to make mobile monitoring very easy,flexible for network transmission
- 5.Multiple control methods:IR remote controller,USB mouse and front panel press button
- 6.Smart video detection:motion detection,video blind,video loss
- 7.Smart camera settings:privacy masking,camera lock,color setting,and tittle display
- 8.Pan Tilt Zoom and Speed Dome Control:more than 60 protocols supported ,preset,scan,auto pan,auto tour,pattern,auxiliary function supported
- 9.Easy backup methods: USB devices,remote network and client software backup
- 10.Alarm triggering screen tips,buzzer,PTZ preset,e-mail &FTP upload
- 11.Smart HDDs Management:non-working HDD hibernation,HDD faulty alarm,Raid function
- 13.Support DHCP / PPPOE / FTP / DNS / DDNS / NTP / Email alarm / IP right management / IP search / network alarm center functions, support web client, standalone client and SDK.
- 14.Enable strong multi-way synchronization with max 1 channel playback, realize the zero-delay between playback channels
15. Support Onvif
16. Support cloud(xmeye.net),no need to do router mapping, just 1 step go to internet with cloud technology

NVR 32 FLUSSI PER TELECAMERE IP MEGAPIXEL

WS-N9232



WS-N9232

Videoregistratore digitale per telecamere IP Megapixel configurabile:

32 flussi 960p (1.3 Megapixel)

24 flussi 1080p (2.0 Megapixel Full-HD)

16 flussi da 3.0 Megapixel

8 flussi da 5.0 Megapixel

Key Features:

Support:

Arabic,Czech,English,Finnish,Greek,Indonesian,Italian,,Japanese,Portuguese,Russian,Thai,T-Chinese,S-

Chinese,Turkish,Brazilian,Bulgarian,Farsi,French,German,Hebrew,Hungarian,Polish,Romanian,Spanish,Swedish,Vietnamese

Support smart mobile and network (IE&Firefox&Safari&Chrome) real time remotely monitoring,such as iPhone,Blackberry,Android,Nokia and windows mobile.

System	Model	WS-N9232
	Main Processor	1 X HI3531
	Operating System	Embedded LINUX
	System Resources	Pentaplex function:live,recording,playback,backup & remote access
	Preview	1/4/8/16/24/32
	Control Device	Front panel,USB mouse,IR remote control
Video	Video Standards	PAL 625 line,50 f/s;NTSC 525 line,60 f/s
	Video Compression	H.264 High profile
	Video Recording	1080P:PAL 1f/s-25f/s NTSC 1f/s-30f/s;
	Motion Detection	Zones:192(16*12)detection zones,Sensitivity:1-6(6 is highest) Trigger recording,PTZ movement,tour,alarm,e-mail& FTP
	TVOutput Audjustment	Adjust TV output color & display zone
Audio	Audio Compression	G711A
	Bidirectional Talk	Support
Record & Playback	Recording Mode	Manual>Alarm>Video Detection>Continuous
	Playback	1/2 /4channel playback simultaneously;
	Search Mode	Time/Date,Alarm,Motion Detection & exact search(accurate to second)
Storage & Backup	Space Occupation	Video: 1080p 80G/day/ch, 720p 26G/day/ch, 960H 24G/day/ch, D1 16~20G/day/ch ; Audio: 691.2M/day/channel
	HDD Management	Hard disk hibernation technology,HDD faulty alarm & Raid(Redundancy)
	Backup Mode	Network download/Flash stick
Interface	Video Input	N/A
	Video Output	2ch BNC output, 1ch VGA output,1ch HDMI
	Audio Input	NO
	Audio Output	1 channel
	Alarm Input	16 channel
	Relay Output	4 channel
	Net Interface	RJ-45 10M/100M/1000M
	PTZ Control	1 RS485, 1 RS232
	3G/WIFI	Support
	USB Interface	2* USB2.0 port for mouse and backup
	Hard Disk	8 SATA port(Max 8 x 4T)
Environmental	Power Supply	Built-in ATX power
	Power Consumption	<10W
	Working Temperature	0-55
	Working Humidity	10%-90%
	Atmosphere Pressure	86kpa-106kpa
	Dimension	L430*W440*H93
	Weight	7.7kg
	Mounting	Desktop