

BL2-58

THERMAL PRINTER 58mm (2 inches)



SANEI

CHARACTERISTICS

- Thermal printer 58mm width (2 inches)
- Tickets and receipts printer
- Compact, light and portable design
- Printing speed : 80mm/sec
- Drop in system for easy paper loading
- Possible wall setting up
- Label printing (optional)
- Colors available : Black and white

DETAILED CHARACTERISTICS

Printing method	Direct line thermal
Number of dots	384dots
Resolution	8dots/mm (203dpi)
Printing/ Paper width	48mm/58mm
Printing speed	80mm/sec max
Character size , Characters / line	FontA 24x12dots (1.5x3.0mm) , 32 characters/line FontB 16x8dots (1.0x2.0mm) , 48 characters/line
Character type	Alphanumeric,International, PC437/850/852/857/858/863/865/866/WPC1252 Katakana
Interface	Serial(RS-232C) / Pararell (Centronics)/ USB (2.0 top speed)
Logo registration	It is available to register the logo data in user memory and flash memory
Barcode	UPC-A/E , JAN13/8 , CODE39 , ITF , CODABAR , CODE128
2-dimensional barcode (option)	QRcode , Maxicode , PDF417 , DataMatrix , MicroPDF417
Input buffer	8k bytes
Emulation	ESC/POS conformity / BL-58 compatible
Operating condition	-10°C-+50°C/10%RH-85%RH (no condensation)
Storage condition	-20°C-+60°C/10%RH-90%RH (no condensation)
Power supply	AC adapter : AC100/120/240V±10% 50/60Hz
Reliability	Life time of head : Wear resistance 50km Pulse resistance 100 million pulse
Dimensions	93×125×70mm (W×D×H)
Weight	265g (paper not included)
EMI conformity	VCCI , CE , FCC
Standard accessory	Paper roll (sample), AC adapter
Optional accessory	Paper roll (sample), AC adapter