

# Proyector Lineal HS 130lm/w



Instalación Suspendida

Diseño Modular, bajo resplandor efecto luminoso 130lm/W, puede ahorrar hasta un 60%.




Instalación en Poste




Sensor Crepuscular


Medidas:(mm/inch) 60W



Medidas:(mm/inch) 100W



Medidas:(mm/inch) 120W



Modelo	CCT	Light output (±10%)lm	CRI
JVJ-LH2F-060-50K-01	5000K	8280	>80
JVJ-LH2F-060-40K-01	4000K	8100	>80
JVJ-LH2F-060-35K-01	3500K	7800	>80
JVJ-LH2F-060-30K-01	3000K	7800	>80
JVJ-LH2F-060-50K-02	5000K	7920	>80
JVJ-LH2F-060-40K-02	4000K	7800	>80
JVJ-LH2F-060-35K-02	3500K	7620	>80
JVJ-LH2F-060-30K-02	3000K	7620	>80

Modelo	CCT	Light output (±10%)lm	CRI
JVJ-LH2F-100-50K-01	5000K	13800	>80
JVJ-LH2F-100-40K-01	4000K	13500	>80
JVJ-LH2F-100-35K-01	3500K	13000	>80
JVJ-LH2F-100-30K-01	3000K	13000	>80
JVJ-LH2F-100-50K-02	5000K	13200	>80
JVJ-LH2F-100-40K-02	4000K	13000	>80
JVJ-LH2F-100-35K-02	3500K	12700	>80
JVJ-LH2F-100-30K-02	3000K	12700	>80

JVJ-LH4F-100-50K-01	5000K	13800	>80
JVJ-LH4F-100-40K-01	4000K	13500	>80
JVJ-LH4F-100-35K-01	3500K	13000	>80
JVJ-LH4F-100-30K-01	3000K	13000	>80
JVJ-LH4F-100-50K-02	5000K	13200	>80
JVJ-LH4F-100-40K-02	4000K	13000	>80
JVJ-LH4F-100-35K-02	3500K	12700	>80
JVJ-LH4F-100-30K-02	3000K	12700	>80

Modelo	CCT	Light output (±10%)lm	CRI
JVJ-LH2F-120-50K-01	5000K	16560	>80
JVJ-LH2F-120-40K-01	4000K	16200	>80
JVJ-LH2F-120-35K-01	3500K	15600	>80
JVJ-LH2F-120-30K-01	3000K	15600	>80
JVJ-LH2F-120-50K-02	5000K	15840	>80
JVJ-LH2F-120-40K-02	4000K	15600	>80
JVJ-LH2F-120-35K-02	3500K	15240	>80
JVJ-LH2F-120-30K-02	3000K	15240	>80

